



# Specifications for Mini Outward Spray Ring:

March, 2010

## **General Structure Design and Construction:**

The Mini Outward Spray Ring is a ground spray element that emits 12 streams of water outward from a 3ft-diameter ring. The feature flow rates can be adjusted to increase or decrease the spray height and projection of the streams. The Spray Ring is designed for wet deck applications with no standing water. The Spray ring to be cast into thickened concrete pad with spray nozzles flush with finished floor. The manufacturer shall supply a complete feature package including: spray ring structure, adjustable & removable spray jets, jet extraction tool and winterization plugs. Pumping system and supply piping with flow control valve to be supplied and installed by others. The Mini Outward Spray Ring is exclusively Manufactured by Aquatic Recreation Company, LLC, Toll Free Phone #877-632-0503, Local Phone #952-445-5135, Fax #952-345-6444, Website: www.arc4waterplay.com.

## **Spray Ring:**

The Mini Outward Spray Ring structure is constructed of heavy duty gas welded PVC material. Structure fittings and connection ports to be gas welded; triple bead fabrication for strength and durability. Spray ring is designed to be completely encapsulated into thickened concrete slab designed by others.

## **Spray Jets:**

Spray jets are manufactured from heavy-duty PVC materials. Spray jets thread into spray ring structure with a jet extraction tool. Spray jets create a clear stream water effect with a design spray height of 5ft.

## **Winterization:**

Mini Outward Spray Ring will be provided with threaded winterization plugs. All water to be evacuated from structure by either blowing out plumbing lines or by gravity draining back to collection tank. Prior to plugging, use of a biodegradable swimming pool anti-freeze is recommended.

## **Colors:**

The top of each jet fitting to be flush with finished floor and be gray in color.

## **Flow Rate Design:**

Feature designed flow rate is available in either High Flow or Low Flow effects as listed below: (select one)

- Feature designed flow rate for this project is **High Flow:** \_\_\_\_\_ **GPM**, which will require a \_\_\_\_\_ **INCH** size pipe feed. This high flow rate will have approximately 1/2" stream effects.
- Feature designed flow rate for this project is **Low Flow:** \_\_\_\_\_ **GPM**, which will require a \_\_\_\_\_ **INCH** size pipe feed. This low flow rate will have approximately 1/4" stream effects.

## **Warranty:**

Product warranty will be a five year warranty against defects in workmanship and materials. All finishes shall have a five year unconditional warranty against rust and corrosion. Warranties exclude normal wear and tear, abuse, improper installation and maintenance.

## **Packaging:**

The Mini Outward Spray Ring shall be packaged with all necessary support and protective wrapping so as to protect during normal shipping and handling. Care must be exercised during handling to avoid damage to product structure and finish.

## **Installation Instructions:**

The Mini Outward Spray Ring will be provided with complete installation drawings and instructions. Please read all installation instructions prior to installation. Installer may call Aquatic Recreation Company LLC at their toll free number #877-632-0503 during installation if there are questions concerning this product.

\* Product specifications subject to change at any time.