



Specifications for Side Wall Fan Spray:

March, 2010

General Structure Design and Construction:

The Side Wall Fan Spray is a ground spray element that emits a sheeting fan water effect in an outward arching pattern. The feature flow rates can be adjusted to increase or decrease fan spray heights and projection. The Side Wall Fan Spray jet pod is to be cast into thickened concrete wall with access cover flush with finished wall. The manufacturer shall supply a complete assembly including: fan spray jet pod, non-slip cover plate, bronze fan spray nozzle, vandal proof stainless steel hardware, and winterization cover plate. Pumping system and supply piping with flow control valve to be supplied and installed by others. The Side Wall Fan Spray is exclusively manufactured by Aquatic Recreation Company, LLC, Toll Free Phone #877-632-0503, Local Phone #952-445-5135, Fax #952-345-6444, Website: www.arc4waterplay.com.

Jet Pod:

The Side Wall Fan Spray jet pod is constructed of heavy-duty PVC plastic material with stainless steel hardware. Structure fittings and connection ports to be gas welded; triple bead fabrication for strength and durability. The jet pod is designed to be completely encapsulated into thickened concrete wall designed by others.

Cover Plate:

The cover plate to be constructed of a heavy-duty PVC plastic material with a colored, non-slip coating. The cover plate is to be secured to jet pod with tamper resistant stainless steel fasteners.

Nozzle:

Side Wall Fan spray nozzle to be a machined bronze fan spray nozzle designed to create a sheeting fan water effect in an outward arching pattern with a designed spray height of 3 ft.

Winterization:

Ground spray embeds will come complete with winterization cover plate. All water to be evacuated from structure by either blowing out plumbing lines or by gravity draining back to collection tank. Prior to plugging use of biodegradable swimming pool anti-freeze is recommended

Colors:

Owner may select colors for the cover plate. Color options are White, Purple, Yellow, Blue, Green, Red, and Orange.

Flow Rate Design:

Feature nominal design flow rate for this project is: _____ *GPM*, which will require a _____ *INCH* size pipe feed with a flow control valve supplied by others.

Warranty:

Product warranty will be a five year warranty against defects in workmanship and materials. All finishes shall have a five year unconditional warranty against rust and corrosion. Warranties exclude normal wear and tear, abuse, improper installation and maintenance.

Packaging:

The Side Wall Fan Spray shall be packaged with all necessary protective wrapping so as to protect during normal shipping and handling. Care must be exercised during handling to avoid damage to product structure and finish.

Installation Instructions:

The Side Wall Fan Spray will be provided with complete installation drawings and instructions. Please read all installation instructions prior to installation. Installer may call Aquatic Recreation Company LLC at their toll free number #877-632-0503 during installation if there are questions concerning this product.

* Product specifications subject to change at any time.