



NOTES

1. Valve must be installed on supply line to regulate flow.
2. Shut off valve must be installed on drain line.
3. Ø12" Concrete mounting surface for structure installation needs to be level & flat.
4. Ø2" Supply line size is based on designed flow rate for structure.
5. Underground plumbing to be designed for winterization.
6. Consult local electrical inspector for grounding.
7. Concrete will need to be cured a minimum of 7 days before installing structure.
8. Product specifications are subject to change.

TOP VIEW




FRONT VIEW



\*\*Not for Construction\*\*

SPLASH ZONE



Splash Zone-Not to Scale

Splash Zone Notes:

Splash zones are approximate, actual splash may vary based on various environmental conditions, flow rates, slope of splash pad and submergence depth.

PRODUCT OPTIONS

Structure:

Structural Plastics Fabrication.  
(see specification for details)

Flow Rate Design:

- High Flow Option Selected.  
(see specification for details on this option)
- Low Flow Option Selected.  
(see specification for details on this option)

DATA

High Flow: 40 to 60 GPM  
 Low Flow: 15 to 20 GPM  
 Supply Line: 2" Pipe  
 Installation: Flange Mount to Concrete



Toll Free: #877-632-0503  
 Local Phone: 952-445-5135  
 Fax: 952-345-6444  
 Website: www.arc4waterplay.com

WATER POST

P.J.  
DRAWN BY

1/4" = 1'-0"  
SCALE

12/11/09  
DATE

This drawing is issued in confidence for engineering information only. This drawing shall remain the property of Aquatic Recreation Company LLC and may not be reproduced, disclosed to a third party, or used to manufacture anything without direct written permission from Aquatic Recreation Company LLC. Unauthorized use shall entitle Aquatic Recreation Company LLC to all damages caused by such user including preparation charges, lost profits, damage to reputation and attorney's fees.