



Specifications for Sit-N-Soaker:

March, 2010

General Structure Design and Construction:

The Sit-N-Soaker is a structure that emits multiple arching streams of water from the top of the bench up, over and onto users seated on the bench. Feature standard height is 2'6" from mounting pad to top of bench. Feature structure is mounted directly to thickened concrete pad designed by others. Feature flow rates can be adjusted to increase or decrease spray height and projection. The manufacturer shall supply a complete assembly including: bench structure, (5) base skirts, anchoring system, fasteners, gaskets, and hardware. Pumping system and supply line with flow control valve to be supplied and installed by others. The Sit-N-Soaker is exclusively manufactured by Aquatic Recreation Company, LLC, Toll Free Phone #877-632-0503, Local Phone #952-445-5135, Fax #952-345-6444, Website: www.arc4waterplay.com.

Structure:

Structure to have (7) components: bench structures and (5) base skirts. These individual components to be assembled in the field with stainless steel hardware and gaskets supplied by the manufacturer.

Bench:

Bench to be fabricated from gas welded from Structural Plastics. Wood slats to be made of durable plastic slats fabricated to resemble wood.

Base Skirt:

Base skirts to be fabricated from durable PVC caps.

Sit-N-Soaker Nozzle:

The Sit-N-Soaker is a proprietary product design that includes an internal distribution nozzle manifold. This Sit-N-Soaker manifold allows for the water to be redirected and evenly proportioned throughout the cross bar to create a more uniform water stream effect.

Finish:

All structure finishes are non-toxic, compatible with chlorinated water, and corrosion resistant. UV stabilizers are added to the finish coat to provide color protection in indoor or outdoor installations.

Colors:

Owner may select colors for each individual component: bench structure and (5) base skirts. Color options are White, Purple, Yellow, Blue, Green, Red, and Orange. Plastic wooden slats to be standard wood color.

Mounting System:

Structure to be anchored to a thickened concrete slab with 5/8-inch stainless steel studs. Studs to be drilled and anchored into place with a fast setting two-part component adhesive per manufacturer installation instruction.

Flow Rate Design:

Feature nominal design flow rate for this project is: _____ *GPM*, which will require a _____ *INCH* size pipe feed with a flow control valve supplied by others.

Warranty:

Product warranty will be a five year warranty against defects in workmanship and materials. All finishes shall have a five year unconditional warranty against rust and corrosion. Warranties exclude normal wear and tear, abuse, improper installation and maintenance.

Packaging:

The Sit-N-Soaker shall be packaged with all necessary support and protective wrapping so as to protect components during normal shipping and handling. Care must be exercised during handling to avoid damage to product structure and finish.

Installation Instructions:

The Sit-N-Soaker will be provided with complete installation drawings and instructions. Please read all installation instructions prior to installation. Installer may call Aquatic Recreation Company at their toll free number #877-632-0503 during installation if there are questions concerning this product.

- Product specifications subject to change at any time.